



ID/IÇ



OD/DÇ



WP/ÇB



BP/PB



BR/KY/r



W/A



L/B

| inch | mm | mm | BAR | PSI | BAR | PSI | mm | gr/mt | mt |
|-------|-------|-----|-----|-----|-----|-----|------|-------|-------------|
| 3/8 | 10 | 17 | 7 | 102 | 21 | 305 | 100 | 228 | 40-46 |
| 1/2 | 12.7 | 20 | 7 | 102 | 21 | 305 | 127 | 274 | 40-46-61 |
| 5/8 | 16 | 23 | 7 | 102 | 21 | 305 | 160 | 330 | 40-46-61 |
| 3/4 | 19 | 27 | 7 | 102 | 21 | 305 | 190 | 433 | 40-46-61 |
| 1 | 25.4 | 33 | 7 | 102 | 21 | 305 | 254 | 540 | 40-46-61 |
| 1 1/4 | 32 | 41 | 7 | 102 | 21 | 305 | 320 | 781 | 40-46-61 |
| 1 1/2 | 38 | 47 | 7 | 102 | 21 | 305 | 380 | 898 | 40-46-61 |
| 1 3/4 | 44.5 | 54 | 7 | 102 | 21 | 305 | 445 | 1142 | 40-46-61 |
| 2 | 51 | 60 | 7 | 102 | 21 | 305 | 510 | 1198 | 40-46-61 |
| 2 1/2 | 63.5 | 74 | 7 | 102 | 21 | 305 | 635 | 1675 | 40-46-61 |
| 2 3/4 | 70 | 82 | 7 | 102 | 21 | 305 | 700 | 2155 | 40-46-61 |
| 3 | 76.2 | 88 | 7 | 102 | 21 | 305 | 762 | 2287 | 40-46-61 |
| 4 | 101.6 | 114 | 7 | 102 | 21 | 305 | 1016 | 3158 | 40-46-61 |
| 5 | 127 | 140 | 7 | 102 | 21 | 305 | 1270 | 3950 | 20-40-46-61 |
| 6 | 152.4 | 165 | 7 | 102 | 21 | 305 | 1524 | 4578 | 20-40-46-61 |
| 8 | 203.2 | 218 | 7 | 102 | 21 | 305 | 2032 | 7480 | 20 |
| 10 | 254 | 270 | 7 | 102 | 21 | 305 | 2540 | 9370 | 10 |